An ISO 9001 : 2015 & GMP Certified Company Office : No 603, 6th Floor, Tardeo AC Market, 87, Tardeo Road, Tardeo, Mumbai, Maharashtra 400034, India (BHARAT)

Tel: +91 98200 41841 Email: info@ottokemi.com Web: www.ottokemi.com

MATERIAL SAFETY DATA SHEET (MSDS)

SECTION 1: Product identifiers

Product Name : Bismuth fluoride

Product Code : B 1849 CAS No: 7787-61-3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use: Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet

Company identification OTTO CHEMIE PVT LTD

No 603, 6th Floor, Tardeo AC Market, 87, Tardeo Road, Tardeo, Mumbai, Maharashtra 400034, India (BHARAT)

1.4. Emergency telephone number

Phone no.: + 91 98200 41841 (10:00 am - 06:00 pm)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Skin corrosion, (Sub-category

1B)

H314: Causes severe skin burns and eye

damage.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram Signal Word

Hazard Statements

H314

Precautionary Statements

P260

P280

P303 + P361 + P353

P304 + P340 + P310

P305 + P351 + P338

P363

Supplemental Hazard

Statements

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

rinsing.

none

Ecological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Strong hydrogen fluoride-releaser

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Causes severe skin burns and eye damage.

Wash contaminated clothing before reuse.

Wear protective gloves/ protective clothing/ eye protection/ face

IF INHALED: Remove person to fresh air and keep comfortable

IF ON SKIN (or hair): Take off immediately all contaminated

for breathing. Immediately call a POISON CENTER/ doctor.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

Do not breathe dust.

clothing. Rinse skin with water.

protection.

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.



An ISO 9001: 2015 & GMP Certified Company Office: No 603, 6th Floor, Tardeo AC Market, 87, Tardeo Road, Tardeo, Mumbai, Maharashtra 400034, India (BHARAT)

Tel: +91 98200 41841 Email: info@ottokemi.com Web: www.ottokemi.com

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula : BiF3
Molecular weight : 265,98 g/mol
CAS-No. : 7787-61-3
EC-No. : 232-124-8

Component		Classification	Concentration
Bismuth trifluoride			
CAS-No. EC-No.	7787-61-3 232-124-8	Skin Corr. 1B; H314	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Hydrofluoric (HF) acid burns require immediate and specialized first aid and medical treatment. Symptoms may be delayed up to 24 hours depending on the concentration of HF. After decontamination with water, further damage can occur due to penetration/absorption of the fluoride ion. Treatment should be directed toward binding the fluoride ion as well as the effects of exposure. Skin exposures can be treated with a 2.5% calcium gluconate gel repeated until burning ceases. More serious skin exposures may require subcutaneous calcium gluconate except for digital areas unless the physician is experienced in this technique, due to the potential for tissue injury from increased pressure. Absorption can readily occur through the subungual areas and should be considered when undergoing decontamination. Prevention of absorption of the fluoride ion in cases of ingestion can be obtained by giving milk, chewable calcium carbonate tablets or Milk of Magnesia to conscious victims. Conditions such as hypocalcemia, hypomagnesemia and cardiac arrhythmias should be monitored for, since they can occur after exposure. First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

First treatment with calcium gluconate paste.In case of skin contact, Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist.

Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section

2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Hydrogen fluoride

Bismuth oxides

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001 : 2015 & GMP Certified Company Office : No 603, 6th Floor, Tardeo AC Market, 87, Tardeo Road, Tardeo, Mumbai, Maharashtra 400034, India (BHARAT)

Tel: +91 98200 41841 Email: info@ottokemi.com Web: www.ottokemi.com

Not combustible.

Ambient fire may liberate hazardous vapours.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Dry.

Do not store in glass

Storage class

Storage class (TRGS 510): 8A: Combustible, corrosive hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm Break through time: 480 min

Material tested: KCL 741 Dermatril® L

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm Break through time: 480 min Material tested:KCL 741 Dermatril® L

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001: 2015 & GMP Certified Company Office: No 603, 6th Floor, Tardeo AC Market, 87, Tardeo Road, Tardeo, Mumbai, Maharashtra 400034, India (BHARAT)

Tel: +91 98200 41841 Email: info@ottokemi.com Web: www.ottokemi.com

Body Protection protective clothing Respiratory protection

required when dusts are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: Filter type P2

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties
a) Physical state powder
b) Color white

c) Odor No data available d) Melting No data available

point/freezing point
e) Initial boiling point
and boiling range

No data available

f) Flammability (solid, No data available gas)

g) Upper/lower flammability or

explosive limits
h) Flash point
i) Autoignition
temperature

Not applicable
No data available

j) Decomposition No data available temperature

k) pH
I) Viscosity

No data available
Viscosity, kinematic: No data available
Viscosity, dynamic: No data available

m) Water solubility
n) Partition coefficient:
No data available
n-octanol/water

o) Vapor pressure
p) Density
Relative density
q) Relative vapor

No data available
No data available
No data available

density
r) Particle
characteristics
No data available

s) Explosive properties
No data available
t) Oxidizing properties
No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Reacts dangerously with glass.

no information available

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001: 2015 & GMP Certified Company Office: No 603, 6th Floor, Tardeo AC Market, 87, Tardeo Road, Tardeo, Mumbai, Maharashtra 400034, India (BHARAT)

Tel: +91 98200 41841 Email: info@ottokemi.com Web: www.ottokemi.com

10.5 Incompatible materials

glass

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Routes of Entry: Absorbed through skin. Dermal contact. Eye contact. Toxicity to Animals:

Oral LD50 Rat: 1500 mg/kg; Dermal LD50 Rabbit: 2000mg/kg

Inhalation LC50 Rat: > 50mg/L.

Chronic Effects on Humans: CARCINOGENIC EFFECTS: Classified None. by NTP, None. by OSHA, None. by NIOSH.

Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant), of inhalation (lung irritant).

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available. Special Remarks on other Toxic Effects on Humans: Not available.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 3260 IMDG: 3260 IATA: 3260

14.2 UN proper shipping name

ADR/RID: CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S. (Bismuth trifluoride) IMDG: CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S. (Bismuth trifluoride) IATA: CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S. (Bismuth trifluoride)

14.3 Transport hazard class(es)

ADR/RID: 8 IMDG: 8 IATA: 8

14.4 Packaging group

ADR/RID: II IMDG: II IATA: II

14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

14.6 Special precautions for user Tunnel restriction code : (E)

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.



An ISO 9001 : 2015 & GMP Certified Company Office : No 603, 6th Floor, Tardeo AC Market, 87, Tardeo Road, Tardeo, Mumbai, Maharashtra 400034, India (BHARAT)

Tel: +91 98200 41841 Email: info@ottokemi.com Web: www.ottokemi.com

Further information: No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No.

1907/2006.

Other regulations

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other Information

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.

