An ISO 9001: 2015 & GMP Certified Company Office: No 603, 6th Floor, Tardeo AC Market, 87, Tardeo Road, Tardeo, Mumbai, Maharashtra 400034, India (BHARAT)

Tel: +91 98200 41841 Email: info@ottokemi.com Web: www.ottokemi.com

MATERIAL SAFETY DATA SHEET (MSDS)

SECTION 1: Product identifiers

Product Name: 1-Butanol, for spectroscopy, 99%+

Product Code: B 2288 CAS No: 71-36-3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use: Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet

Company identification OTTO CHEMIE PVT LTD

No 603, 6th Floor, Tardeo AC Market, 87, Tardeo Road, Tardeo, Mumbai, Maharashtra 400034, India (BHARAT)

1.4. Emergency telephone number

Phone no.: + 91 98200 41841 (10:00 am - 06:00 pm)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 3), H226 Acute toxicity, Oral (Category 4), H302 Skin irritation (Category 2), H315

Serious eye damage (Category 1), H318

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

Signal Word Danger Hazard statement(s)

H226 Flammable liquid and vapor.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H318 Causes serious eye damage.

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.
P233 Keep container tightly closed.

P280 Wear protective gloves/ protective clothing/ eye protection/ face

protection.

P301 + P312 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel

unwell.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue

rinsing.

Supplemental Hazard

Statements none

Reduced Labeling (<= 125 ml)

Pictogram

Signal Word Danger

Hazard statement(s)

H318 Causes serious eve damage.

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001: 2015 & GMP Certified Company
Office: No 603, 6th Floor, Tardeo AC Market, 87, Tardeo Road,
Tardeo, Mumbai, Maharashtra 400034, India (BHARAT)

Tel: +91 98200 41841 Email: info@ottokemi.com Web: www.ottokemi.com

Precautionary statement(s)

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

Supplemental Hazard

Statements

none

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Toxicological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Butyl alcohol n-Butanol

Formula : C4H10O

Molecular weight : 74,12 g/mol

CAS-No. : 71-36-3

EC-No. : 200-751-6

Component		Classification	Concentration
n-butanol			671
CAS-No.	71-36-3	Flam. Liq. 3; Acute Tox. 4; Skin Irrit. 2;	<= 100 %
EC-No.	200-751-6	Eye Dam. 1; STOT SE 3; H226, H302,	
		H315, H318, H336, H335 Concentration	
	- 33	limits: >= 20 %: STOT SE 3, H335; >=	
S)		20 %: STOT SE 3, H336;	

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with

water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist.

Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section

2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001 : 2015 & GMP Certified Company Office : No 603, 6th Floor, Tardeo AC Market, 87, Tardeo Road, Tardeo, Mumbai, Maharashtra 400034, India (BHARAT)

Tel: +91 98200 41841 Email: info@ottokemi.com Web: www.ottokemi.com

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Flash back possible over considerable distance.

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by

keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®).

Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Handle and store under inert gas. hygroscopic

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.



An ISO 9001: 2015 & GMP Certified Company
Office: No 603, 6th Floor, Tardeo AC Market, 87, Tardeo Road,
Tardeo, Mumbai, Maharashtra 400034, India (BHARAT)

Tel: +91 98200 41841 Email: info@ottokemi.com Web: www.ottokemi.com

SECTION 8: Exposure controls/personal protection

8.1 Control parameters Ingredients with workplace control parameters Derived No Effect Level (DNEL)

Application Area	Routes of exposure	Health effect	Value
Worker DNEL, longterm	inhalation	Local effects	310 mg/m3
Consumer DNEL, longterm	inhalation	Local effects	55 mg/m3
Consumer DNEL, longterm	oral	Systemic effects	

Predicted No Effect Concentration (PNEC)

Compartment	Value	
Fresh water	0,082 mg/l	
Fresh water sediment	0,178 mg/kg	
Sea water	0,0082 mg/l	
Sea sediment	0,0178 mg/kg	
Aquatic intermittent release	2,25 mg/l	
Sewage treatment plant	2476 mg/l	
Soil	0,015 mg/kg	

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,4 mm Break through time: 480 min

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact Material: Chloroprene

Minimum layer thickness: 0,65 mm Break through time: 120 min Material tested:KCL 720 Camapren®

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic

compounds

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001: 2015 & GMP Certified Company Office: No 603, 6th Floor, Tardeo AC Market, 87, Tardeo Road, Tardeo, Mumbai, Maharashtra 400034, India (BHARAT)

Tel: +91 98200 41841 Email: info@ottokemi.com Web: www.ottokemi.com

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties a) Physical state liquid, clear b) Color colorless

c) Odor ethanolic d) Melting

Melting point/range: -90 °C point/freezing point

e) Initial boiling point 116 - 118 °C and boiling range f) Flammability (solid, No data available

gas) g) Úpper/lower Upper explosion limit: 11,2 %(V)

flammability or Lower explosion limit: 1,4 %(V) explosive limits

h) Flash point 35 °C - Pensky-Martens closed cup - ISO 2719 i) Autoignition No data available

temperature j) Decomposition No data available temperature

k) pH 7 at 70 g/l at 20 °C I) Viscosity Viscosity, kinematic: No data available Viscosity, dynamic: 2,95 mPa.s at 20 °C m) Water solubility 66 g/l at 20 °C - OECD Test Guideline 105

n) Partition coefficient: log Pow: 1 at 25 °C - Bioaccumulation is not expected. n-octanol/water

< 10 hPa at 20 °C 0,81 g/mL at 25 °C No data available No data available

No data available

No data available

characteristics s) Explosive properties

Surface tension 69,9 mN/m at 1g/l at 20 °C

- OECD Test Guideline 115

Relative vapor density

o) Vapor pressure p) Density

Relative density

density r) Particle

q) Relative vapor

2,56 at 20 °C - (Air = 1.0)

t) Oxidizing properties 9.2 Other safety information

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapor/air-mixtures are explosive at intense warming.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:

strong oxidising agents

chromium(VI) oxide

Exothermic reaction with:

Alkali metals

Alkaline earth metals

Aluminum

strong reducing agents

Acid chlorides

10.4 Conditions to avoid Exposure to moisture.

Heating.

DISCI AIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001 : 2015 & GMP Certified Company Office : No 603, 6th Floor, Tardeo AC Market, 87, Tardeo Road, Tardeo, Mumbai, Maharashtra 400034, India (BHARAT)

Tel: +91 98200 41841 Email: info@ottokemi.com Web: www.ottokemi.com

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Routes of Entry: Absorbed through skin. Dermal contact. Eye contact. Toxicity to Animals:

Oral LD50 Rat: 1500 mg/kg; Dermal LD50 Rabbit: 2000mg/kg

Inhalation LC50 Rat: > 50mg/L.

Chronic Effects on Humans: CARCINOGENIC EFFECTS: Classified None. by NTP, None. by OSHA, None. by NIOSH.

Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant), of inhalation (lung irritant).

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available. Special Remarks on other Toxic Effects on Humans: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish static test LC50 - Pimephales promelas (fathead minnow) - 1.376

mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia

and other aquatic

invertebrates

static test EC50 - Daphnia magna (Water flea) - 1.328 mg/l - 48 h

(OECD Test Guideline 202)

Toxicity to algae static test ErC50 - Pseudokirchneriella subcapitata (green algae) -

225 mg/l - 96 h

(OECD Test Guideline 201)

Toxicity to bacteria static test EC50 - Pseudomonas putida - 4.390 mg/l - 17 h

(DIN 38421 TEIL 8)

Toxicity to daphnia

and other aquatic

invertebrates(Chronic

toxicity)

semi-static test EC50 - Daphnia magna (Water flea) - 18 mg/l - 21 d

(OECD Test Guideline 211)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 20 d

Result: 92 % - Readily biodegradable.

Remarks: (ECHA)

Ratio BOD/ThBOD 33 %

Remarks: (IUCLID)

12.3 Bioaccumulative potential

Bioaccumulation Oncorhynchus mykiss (rainbow trout) - 24 h

- 921 mg/l(n-butanol)

Bioconcentration factor (BCF): 0,38

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent,

bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at

levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001: 2015 & GMP Certified Company Office: No 603, 6th Floor, Tardeo AC Market, 87, Tardeo Road, Tardeo, Mumbai, Maharashtra 400034, India (BHARAT)

Tel: +91 98200 41841 Email: info@ottokemi.com Web: www.ottokemi.com

12.7 Other adverse effects No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

No data available

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1120 IMDG: 1120 IATA: 1120

14.2 UN proper shipping name

ADR/RID: BUTANOLS IMDG: BUTANOLS IATA: BUTANOLS

14.3 Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

ADR/RID: III IMDG: III IATA: III

14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

14.6 Special precautions for user Tunnel restriction code : (D/E) Further information : No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No.

1907/2006.

Authorisations and/or restrictions on use

National legislation

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Other regulations

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or

stricter national regulations where applicable.

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other Information

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.