

OTTO CHEMIE PVT LTD

An ISO 9001 : 2015 & GMP Certified Company
101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate,
Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841
Email : info@ottokemi.com Web : www.ottokemi.com

MATERIAL SAFETY DATA SHEET (MSDS)

SECTION 1: Product identifiers

Product Name : sec-Butyllithium solution, 1.4 M in cyclohexane
Product Code: B 7083
CAS-No.: 598-30-1

1.2. Relevant identified uses of the substance or mixture and uses advised against
Use : Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet

Company identification
OTTO CHEMIE PVT LTD
101, Aarkay Ruby Industrial Estate(1B), Opp Shree Narayan Industrial Estate,
Chinchpada, Vasai East, Waliv, Maharashtra 401208.
Email info@ottokemi.com

1.4. Emergency telephone number

Phone no. : + 91 22 2207 0099 (9:00am - 6:00 pm)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Flammable liquids, (Category 2)

Pyrophoric liquids, (Category 1)
exposed to air.

Substances and mixtures which
in contact with water emit
flammable gases, (Category 1)

Skin corrosion, (Sub-category

1B)

Serious eye damage, (Category
1)

Specific target organ toxicity -
single exposure, (Category 3),
Central nervous system

Aspiration hazard, (Category 1)
airways.

Short-term (acute) aquatic
hazard, (Category 1)

Long-term (chronic) aquatic

hazard, (Category 1)

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

Signal Word

Hazard Statements

H225

H250

H260

H304

H314

H336

H410

Precautionary Statements

P210

P231 + P232

H225: Highly flammable liquid and vapor.
H250: Catches fire spontaneously if

H260: In contact with water releases
flammable gases which may ignite
spontaneously.

H314: Causes severe skin burns and eye
damage.

H318: Causes serious eye damage

H336: May cause drowsiness or dizziness.

H304: May be fatal if swallowed and enters

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long
lasting effects.

Danger

Highly flammable liquid and vapor.

Catches fire spontaneously if exposed to air.

In contact with water releases flammable gases which may
ignite spontaneously.

May be fatal if swallowed and enters airways.

Causes severe skin burns and eye damage.

May cause drowsiness or dizziness.

Very toxic to aquatic life with long lasting effects.

Keep away from heat, hot surfaces, sparks, open flames and
other ignition sources. No smoking.

Handle and store contents under inert gas. Protect from

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy.

This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

OTTO CHEMIE PVT LTD

An ISO 9001 : 2015 & GMP Certified Company
101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate,
Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841
Email : info@ottokemi.com Web : www.ottokemi.com

P280	moisture. Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P330 + P331 P303 + P361 + P353	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Supplemental Hazard Statements	none
Reduced Labeling (<= 125 ml)	
Pictogram	
Signal Word	Danger
Hazard Statements	
H250	Catches fire spontaneously if exposed to air.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
Precautionary Statements	
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P330 + P331 P303 + P361 + P353	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Supplemental Hazard Statements	none
2.3 Other hazards	
This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.	
Ecological information:	
The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.	
Toxicological information:	
The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.	

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Synonyms : Lithium-2-butanide
s-BuLi
Formula : C₄H₉Li
Molecular weight : 64,06 g/mol

Component	Classification	Concentration
sec-Butyllithium		
CAS-No. 598-30-1	Pyr. Liq. 1; Water-react 1;	>= 10 - < 20
EC-No. 209-927-7	Skin Corr. 1B; H250, H260, H314	%

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy.

This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

OTTO CHEMIE PVT LTD

An ISO 9001 : 2015 & GMP Certified Company
101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate,
Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841
Email : info@ottokemi.com Web : www.ottokemi.com

*A registration number is not available for this substance as the substance or its use are exempted from registration according to Article 2 REACH Regulation (EC) No 1907/2006, or the annual tonnage does not require a registration.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist.

Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Pulmonary failure possible after aspiration of vomit. Call a physician immediately. Do not attempt to neutralise.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

Water Foam

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

May not get in touch with: Water

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g.

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy.

This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

OTTO CHEMIE PVT LTD

An ISO 9001 : 2015 & GMP Certified Company
101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate,
Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841
Email : info@ottokemi.com Web : www.ottokemi.com

Chemizorb®). Dispose of properly. Clean up affected area.
6.4 Reference to other sections
For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Keep workplace dry. Do not allow product to come into contact with water.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep away from heat and sources of ignition.

Never allow product to get in contact with water during storage.

Storage stability Recommended storage temperature

2 - 8 °C

Air sensitive. Handle and store under inert gas.

Storage class

Storage class (TRGS 510): 4.2: Pyrophoric and self-heating hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm

Break through time: 480 min

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm

Break through time: 480 min

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy.

This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

OTTO CHEMIE PVT LTD

An ISO 9001 : 2015 & GMP Certified Company
101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate,
Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841
Email : info@ottokemi.com Web : www.ottokemi.com

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: Filter type ABEK

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Physical state	liquid
b) Color	colorless, to, yellow
c) Odor	No data available
d) Melting point/freezing point	No data available
e) Initial boiling point and boiling range	No data available
f) Flammability (solid, gas)	No data available
g) Upper/lower flammability or explosive limits	No data available
h) Flash point -	17 °C - closed cup
i) Autoignition temperature	No data available
j) Decomposition temperature	No data available
k) pH	No data available
l) Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: No data available
m) Water solubility	No data available
n) Partition coefficient: n-octanol/water	No data available
o) Vapor pressure	No data available
p) Density	0,769 g/cm ³
Relative density	No data available
q) Relative vapor density	No data available
r) Particle characteristics	No data available
s) Explosive properties	Not classified as explosive.
t) Oxidizing properties	none

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

Sensitive to air.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Exposure to air.

Warming.

Moisture.

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy.

This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

OTTO CHEMIE PVT LTD

An ISO 9001 : 2015 & GMP Certified Company
101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate,
Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841
Email : info@ottokemi.com Web : www.ottokemi.com

10.5 Incompatible materials

Water, Strong oxidizing agents, Alcohols, acids

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Routes of Entry: Absorbed through skin. Dermal contact. Eye contact. Toxicity to Animals:

Oral LD50 Rat: 1500 mg/kg; Dermal LD50 Rabbit: 2000mg/kg

Inhalation LC50 Rat: > 50mg/L.

Chronic Effects on Humans: CARCINOGENIC EFFECTS: Classified None. by NTP, None. by OSHA, None. by NIOSH.

Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant), of inhalation (lung irritant).

Special Remarks on Toxicity

to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Mixture

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment :

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

Components

Cyclohexane

Toxicity to fish flow-through test LC50 - Pimephales promelas (fathead

minnow) - 4,53 mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia

and other aquatic

invertebrates

static test EC50 - Daphnia magna (Water flea) - 0,9 mg/l - 48

h

(OECD Test Guideline 202)

Toxicity to algae ErC50 - Pseudokirchneriella subcapitata (green algae) - >

4,425 mg/l - 72 h

(OECD Test Guideline 201)

Toxicity to bacteria IC50 - Bacteria - 29 mg/l - 15 h

Remarks: (ECHA)

sec-Butyllithium

No data available

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy.

This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

