An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841 Email : <u>info@ottokemi.com</u> Web : <u>www.ottokemi.com</u>

MATERIAL SAFETY DATA SHEET (MSDS)

SECTION 1. Product identifiers

Product name: 1,4-Dioxan, for HPLC, 99%+ Product Code: D 2239 CAS No : 123-91-1

1.2. Relevant identified uses of the substance or mixture and uses advised against Use : Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet
Company identification
OTTO CHEMIE PVT LTD
101, Aarkay Ruby Industrial Estate(1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208.
Email <u>info@ottokemi.com</u>

1.4. Emergency telephone number Phone no. : + 91 22 2207 0099 (9:00am - 6:00 pm)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Flammable liquids, (Category 2) Eye irritation, (Category 2) Carcinogenicity, (Category 1B) Specific target organ toxicity single exposure, (Category 3), Respiratory system 2.2 Label elements Labelling according Regulation (EC) No 1272/2008 Pictogram Signal Word Hazard Statements H225 H319 H335 H350 **Precautionary Statements** P202 P210 P233

P233 P240 P305 + P351 + P338

P308 + P313 Supplemental Hazard information (EU) EUH019 EUH066

Reduced Labeling (<= 125 ml) Pictogram Signal Word Hazard Statements H350 Precautionary Statements P202 H225: Highly flammable liquid and vapor. H319: Causes serious eye irritation. H350: May cause cancer. H335: May cause respiratory irritation.

Danger

Highly flammable liquid and vapor. Causes serious eye irritation. May cause respiratory irritation. May cause cancer.

Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/ attention. May form explosive peroxides. Repeated exposure may cause skin dryness or cracking. Restricted to professional users.

Danger

May cause cancer.

Do not handle until all safety precautions have been read and understood.

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841 Email : info@ottokemi.com Web : www.ottokemi.com

P308 + P313 Supplemental Hazard information (EU) EUH019 EUH066

IF exposed or concerned: Get medical advice/ attention.

May form explosive peroxides. Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards This substance/mixture contains no components considered to be either persistent.

bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at

levels of 0.1% or higher.

Ecological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Toxicological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms	: Dioxane	
	Diethylene oxide	
Formula	: C4H8O2	
Molecular weight	: 88,11 g/mol	
CAS-No.	: 123-91-1	
EC-No.	: 204-661-8	

Component	Classification	Concentration
1,4-Dioxane Included in the Candidate List of Substances of Very High Concern (SVHC) according to Regulation (EC) No. 1907/2006 (REACH)	The C	
CAS-No. 123-91-1 EC-No. 204-661-8	Flam. Liq. 2; Eye Irrit. 2; Carc. 1B; STOT SE 3; H225, H319, H350, H335 Concentration limits: >= 20 %: STOT SE 3, H335;	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with

water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact

lenses.

If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841 Email : info@ottokemi.com Web : www.ottokemi.com

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media Water Foam Carbon dioxide (CO2) Dry powder Unsuitable extinguishing media For this substance/mixture no limitations of extinguishing agents are given. 5.2 Special hazards arising from the substance or mixture Carbon oxides Combustible. Pav attention to flashback. Vapors are heavier than air and may spread along floors. Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures. 5.3 Advice for firefighters Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing. 5.4 Further information Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system. **SECTION 6: Accidental release measures** 6.1 Personal precautions, protective equipment and emergency procedures Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8. 6.2 Environmental precautions Do not let product enter drains. Risk of explosion. 6.3 Methods and materials for containment and cleaning up Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area. 6.4 Reference to other sections For disposal see section 13. **SECTION 7: Handling and storage** 7.1 Precautions for safe handling Advice on safe handling Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols. Advice on protection against fire and explosion Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge. Hygiene measures Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2. 7.2 Conditions for safe storage, including any incompatibilities Storage conditions Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons. . Test for peroxide formation periodically and before distillation. Storage class Storage class (TRGS 510): 3: Flammable liquids 7.3 Specific end use(s) Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841 Email : <u>info@ottokemi.com</u> Web : <u>www.ottokemi.com</u>

SECTION 8: Exposure controls/personal protection

8.1 Control parameters Ingredients with workplace control parameters Derived No Effect Level (DNEL)

Application Area	Routes of exposure	Health effect	Value
Workers	Inhalation	Long-term local effects	144 mg/m3
Workers	Inhalation	Long-term systemic effects	73 mg/m3
Workers	Skin contact	Long-term systemic effects	21 mg/m3

Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	0,153 mg/kg
Sea water	0,67 mg/l
Fresh water	10 mg/l
Fresh water sediment	37 mg/kg
Sewage treatment plant	2700 mg/l
Aquatic intermittent release	10 mg/

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0,7 mm

Break through time: 480 min

Material tested:Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact

Material: Viton®

Minimum layer thickness: 0,7 mm

Break through time: 120 min

Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic

compounds

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

DISCLAIMER

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841 Email : <u>info@ottokemi.com</u> Web : <u>www.ottokemi.com</u>

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Physical state b) Color c) Odor d) Melting point/freezing point e) Initial boiling point and boiling range f) Flammability (solid. gas) g) Upper/lower flammability or explosive limits h) Flash point i) Autoignition temperature j) Decomposition temperature k) Ph I) Viscosity

m) Water solubilityn) Partition coefficient:n-octanol/watero) Vapor pressure

p) Density Relative density q) Relative vapor density r) Particle characteristics s) Explosive properties t) Oxidizing properties 9.2 Other safety information Surface tension Relative vapor density

SECTION 10: Stability and reactivity

10.1 Reactivity Formation of peroxides possible. Vapors may form explosive mixture with air. 10.2 Chemical stability The product is chemically stable under standard ambient conditions (room temperature). Stable under recommended storage conditions. Contains the following stabilizer(s): butyl hydroxytoluene (BHT) (0,0025 %) 10.3 Possibility of hazardous reactions No data available 10.4 Conditions to avoid Warming. Moisture. 10.5 Incompatible materials No data available 10.6 Hazardous decomposition products Peroxides In the event of fire: see section 5

DISCLAIMER

liquid colorless No data available Melting point/range: 10 - 12 °C - lit.

100 - 102 °C - lit.

No data available

Upper explosion limit: 22 %(V) Lower explosion limit: 2 %(V)

11 °C - closed cup 190,55 °C

No data available

6,0 - 8 at 500 g/l at 20 °C Viscosity, kinematic: 1,27 mm2/s at 20 °C - OECD Test Guideline 1140,93 mm2/s at 40 °C - OECD Test Guideline 114 Viscosity, dynamic: 1,2 mPa.s at 25 °C1,32 mPa.s at 20 °C 1.000 g/l at 20 °C - completely miscible log Pow: -0,42 - Bioaccumulation is not expected.

36 hPa at 20 °C 53 hPa at 25,20 °C 1,034 g/cm3 at 25 °C - lit. 1,03 at 20 °C 3,04 - (Air = 1.0)

No data available

No data available none 36,9 mN/m at 25 °C

3,04 - (Air = 1.0)

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841 Email : info@ottokemi.com Web : www.ottokemi.com

SECTION 11: Toxicological information

11.1 Information on toxicological effects Routes of Entry: Absorbed through skin. Dermal contact. Eye contact. Toxicity to Animals: Oral LD50 Rat: 1500 mg/kg; Dermal LD50 Rabbit: 2000mg/kg Inhalation LC50 Rat: > 50mg/L. Chronic Effects on Humans: CARCINOGENIC EFFECTS: Classified None. by NTP, None. by OSHA, None. by NIOSH. Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant), of inhalation (lung irritant). Special Remarks on Toxicity to Animals: Not available. Special Remarks on other Toxic Effects on Humans: Not available. Special Remarks on other Toxic Effects on Humans: Not available.

SECTION 12: Ecological information

12.1 Toxicity Toxicity to daphnia and other aquatic invertebrates semi-static test EC50 - Daphnia magna (Water flea) - > 1.000 mg/l - 48 h (OECD Test Guideline 202) Toxicity to algae static test ErC50 - Pseudokirchneriella subcapitata (green algae) - > 1.000 mg/l - 72 h (OECD Test Guideline 201) Toxicity to fish(Chronic toxicity) flow-through test NOEC - Pimephales promelas (fathead minnow) - > 103 mg/l - 32 d Remarks: (ECHA) Toxicity to daphnia and other aquatic invertebrates(Chronic toxicity) NOEC - Daphnia magna (Water flea) - 1.000 mg/l - 21 d (OECD Test Guideline 211) 12.2 Persistence and degradability Biodegradability aerobic - Exposure time 29 d Result: < 10 % - Not readily biodegradable. (OECD Test Guideline 301F) 12.3 Bioaccumulative potential Bioaccumulation Cyprinus carpio (Carp) - 10 mg/l(1,4-Dioxane) Bioconcentration factor (BCF): 0,3 - 0,7 (OECD Test Guideline 305C) 12.4 Mobility in soil No data available 12.5 Results of PBT and vPvB assessment This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. 12.6 Endocrine disrupting properties Product: : The substance/mixture does not contain components Assessment considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. 12.7 Other adverse effects Forms toxic mixtures in water, dilution measures notwithstanding.

Discharge into the environment must be avoided.

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841 Email : <u>info@ottokemi.com</u> Web : <u>www.ottokemi.com</u>

IATA: 1165

IATA: 3

IATA: II

IATA: no

SECTION 13: Disposal considerations

13.1 Waste treatment methods No data available

SECTION 14: Transport information 14.1 UN number IMDG: 1165 ADR/RID: 1165 14.2 UN proper shipping name ADR/RID DIOXANE : DIOXANE IMDG ΙΑΤΑ : Dioxane 14.3 Transport hazard class(es) ADR/RID: 3 IMDG: 3 14.4 Packaging group ADR/RID: II IMDG: II 14.5 Environmental hazards ADR/RID: no IMDG Marine pollutant: no 14.6 Special precautions for user Tunnel restriction code : (D/E) Further information : No data available **SECTION 15: Regulatory information** 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. Authorisations and/or restrictions on use REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : 1,4-Dioxane REACH - Restrictions on the manufacture,

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : 1,4-Dioxane National legislation Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS Other regulations Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable.

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has been carried out for this substance.

Section 16: Other Information

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.

DISCLAIMER

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.