

# OTTO CHEMIE PVT LTD

An ISO 9001 : 2015 & GMP Certified Company  
101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate,  
Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841  
Email : [info@ottokemi.com](mailto:info@ottokemi.com) Web : [www.ottokemi.com](http://www.ottokemi.com)

---

## MATERIAL SAFETY DATA SHEET (MSDS)

### SECTION 1. Product identifiers

Product name: 1,6-Hexanediol, 99%  
Product Code: H 1372  
CAS No : 629-11-8

1.2. Relevant identified uses of the substance or mixture and uses advised against  
Use : Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet

Company identification  
OTTO CHEMIE PVT LTD  
101, Aarkay Ruby Industrial Estate(1B), Opp Shree Narayan Industrial Estate,  
Chinchpada, Vasai East, Waliv, Maharashtra 401208.  
Email [info@ottokemi.com](mailto:info@ottokemi.com)

1.4. Emergency telephone number

Phone no. : + 91 22 2207 0099 (9:00am - 6:00 pm)

### SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

2.2 Label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Hexamethylene glycol

Formula : C<sub>6</sub>H<sub>14</sub>O<sub>2</sub>

Molecular weight : 118,17 g/mol

CAS-No. : 629-11-8

EC-No. : 211-074-0

No components need to be disclosed according to the applicable regulations.

### SECTION 4: First aid measures

4.1 Description of first-aid measures

If inhaled

After inhalation: fresh air.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most). Consult doctor if feeling unwell.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

---

### DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy.

This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

# OTTO CHEMIE PVT LTD

An ISO 9001 : 2015 & GMP Certified Company  
101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate,  
Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841  
Email : [info@ottokemi.com](mailto:info@ottokemi.com) Web : [www.ottokemi.com](http://www.ottokemi.com)

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO<sub>2</sub>) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

### 5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air on intense heating.

Development of hazardous combustion gases or vapours possible in the event of fire.

### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

### 5.4 Further information

Prevent fire extinguishing water from contaminating surface water or the ground water system.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

### 6.2 Environmental precautions

Do not let product enter drains.

### 6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

### 6.4 Reference to other sections

For disposal see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Dry.

Storage class

Storage class (TRGS 510): 11: Combustible Solids

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Ingredients with workplace control parameters

### 8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm

Break through time: 480 min

---

## DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy.

This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

# OTTO CHEMIE PVT LTD

An ISO 9001 : 2015 & GMP Certified Company  
101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate,  
Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841  
Email : [info@ottokemi.com](mailto:info@ottokemi.com) Web : [www.ottokemi.com](http://www.ottokemi.com)

Material tested:KCL 741 Dermatril® L

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm

Break through time: 480 min

Material tested:KCL 741 Dermatril® L

Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains.

## SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Physical state

flakes

b) Color

white

c) Odor

No data available

d) Melting

Melting point/range: 38 - 42 °C - lit.

point/freezing point

250 °C - lit.

e) Initial boiling point

and boiling range

No data available

f) Flammability (solid, gas)

Upper explosion limit: 16 %(V)  
Lower explosion limit: 6,6 %(V)

g) Upper/lower flammability or explosive limits

h) Flash point

102 °C - closed cup

i) Autoignition

320 °C

temperature

at 1.013 hPa

j) Decomposition

No data available

temperature

k) pH

5,7 at 500 g/l at 20 °C

l) Viscosity

Viscosity, kinematic: No data available

Viscosity, dynamic: No data available

1.000 g/l at 20 °C

log Pow: 0 at 25 °C - Bioaccumulation is not expected.

m) Water solubility

n) Partition coefficient: n-octanol/water

o) Vapor pressure

< 0,01 hPa at 20 °C

p) Density

0,96 g/cm<sup>3</sup> at 20 °C

Relative density

No data available

q) Relative vapor density

No data available

r) Particle

No data available

characteristics

s) Explosive properties

No data available

t) Oxidizing properties

none

9.2 Other safety information

No data available

## SECTION 10: Stability and reactivity

10.1 Reactivity

Forms explosive mixtures with air on intense heating.

A range from approx. 15 Kelvin below the flash point is to be rated as critical.

### DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy.

This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

# OTTO CHEMIE PVT LTD

An ISO 9001 : 2015 & GMP Certified Company  
101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate,  
Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841  
Email : [info@ottokemi.com](mailto:info@ottokemi.com) Web : [www.ottokemi.com](http://www.ottokemi.com)

---

The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.

## 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

## 10.3 Possibility of hazardous reactions

Violent reactions possible with:

Strong oxidizing agents

## 10.4 Conditions to avoid

Strong heating.

## 10.5 Incompatible materials

Strong oxidizing agents

## 10.6 Hazardous decomposition products

In the event of fire: see section 5

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Routes of Entry: Absorbed through skin. Dermal contact. Eye contact. Toxicity to Animals:

Oral LD50 Rat: 1500 mg/kg; Dermal LD50 Rabbit: 2000mg/kg

Inhalation LC50 Rat: > 50mg/L.

Chronic Effects on Humans: CARCINOGENIC EFFECTS: Classified None. by NTP, None. by OSHA, None. by NIOSH.

Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant), of inhalation (lung irritant).

Special Remarks on Toxicity

to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans: Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxicity to fish static test LC50 - *Leuciscus idus* (Golden orfe) - 4.640 - 10.000 mg/l - 96 h

(DIN 38412)

static test NOEC - *Leuciscus idus* (Golden orfe) - 2.200 mg/l - 96 h

(DIN 38412)

Toxicity to daphnia

and other aquatic

invertebrates

static test EC50 - *Daphnia magna* (Water flea) - > 500 mg/l - 48 h

(Regulation (EC) No. 440/2008, Annex, C.2)

Toxicity to algae static test EC50 - *Desmodesmus subspicatus* (green algae) - 5.940 mg/l - 72 h

### 12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d

Result: 95 % - Readily biodegradable.

(OECD Test Guideline 301C)

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

---

## DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy.

This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

# OTTO CHEMIE PVT LTD

An ISO 9001 : 2015 & GMP Certified Company  
101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate,  
Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841  
Email : [info@ottokemi.com](mailto:info@ottokemi.com) Web : [www.ottokemi.com](http://www.ottokemi.com)

---

No data available

## SECTION 13: Disposal considerations

13.1 Waste treatment methods

No data available

## SECTION 14: Transport information

14.1 UN number

ADR/RID: -

IMDG: -

IATA: -

14.2 UN proper shipping name

ADR/RID : Not dangerous goods

IMDG : Not dangerous goods

IATA : Not dangerous goods

14.3 Transport hazard class(es)

ADR/RID: -

IMDG: -

IATA: -

14.4 Packaging group

ADR/RID: -

IMDG: -

IATA: -

14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA: no

14.6 Special precautions for user

No data available

Further information

Not classified as dangerous in the meaning of transport regulations.

## SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

## SECTION 16: Other Information

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.

---

## DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy.

This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product